
Subject: Incorrect CSS settings

Posted by [ljkbrost](#) on Fri, 14 Apr 2006 06:08:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

I run my apache server on `http://localhost:8080` and I found a problem with the XML that gets sent to the client. It looks like the system is not sending the port for the machine.

```
<cssfiles> <filename>HTTP://localhost/radicore/style_default.css</filename>
<filename>HTTP://localhost/radicore/menu/style_custom.css</filename>
</cssfiles>
```

I have traced the problem to `include.xml.php?.inc` inside of the `setCSSfiles(...)` function. When building the filename values the string building function uses `$_SERVER['SERVER_NAME']` when it should use `$_SERVER['HTTP_HOST']`.

Altering the code to the following resolved my problems:

```
// if no custom stylesheet is specified use 'style_custom.css' in local directory
if (empty($css_files)) {
    $css_files[] = 'HTTP://' . $_SERVER['HTTP_HOST'] . dirname($_SERVER['PHP_SELF'])
    . '/style_custom.css';
} // if

// prepend the default stylesheet name from base directory
$dir = getParentDIR();
if (!empty($_SERVER['HTTPS'])) {
    $default_css = 'HTTP://' . $_GLOBALS['https_server'] . $_GLOBALS['https_server_suffix'] . $dir
    . '/style_default.css';
} else {
    $default_css = 'HTTP://' . $_SERVER['HTTP_HOST'] . $dir . '/style_default.css';
} // if
```

Cheers,

Kyle Brost
