Subject: Problem with IIS Posted by theos on Mon, 17 Dec 2007 17:18:58 GMT View Forum Message <> Reply to Message

First, i'm sorry my bad english.

In radicore v1.18.0 released:

fixed bug in the logon screen when run with Microsoft IIS which caused it to use HTTPS even when an HTTPS server had not been specified.

In my case, v1.18 and v1.31, the logon screen not applied css, and the next screen link to https.

My solution:/includes/config.inc \$_SERVER['HTTPS']="";

The reason: In/includes/include.xml.php5.inc if (!empty(\$_SERVER['HTTPS'])) It was always true

In manual php:

\$_SERVER['HTTPS']

Set to a non-empty value if the script was queried through the HTTPS protocol. Note that when using ISAPI with IIS, the value will be off if the request was not made through the HTTPS protocol.

Is there another solution?

Thanks and congratulation for this great work.

Subject: Re: Problem with IIS Posted by AJM on Mon, 17 Dec 2007 18:07:51 GMT View Forum Message <> Reply to Message

It is always a problem when different web servers produce different results.

I have amended the code inside initSession() so that if \$_SERVER['HTTPS'] is empty it will be set to 'off', and each line which reads if (!empty(\$_SERVER['HTTPS'])) { has been changed to if (is_True(\$_SERVER['HTTPS'])) { These fives are in the attached file, so can you try them and let ma know how you get on?

These fixes are in the attached file, so can you try them and let me know how you get on?.

File Attachments
1) includes-2007-12-17.zip, downloaded 1333 times

Subject: Re: Problem with IIS Posted by theos on Mon, 17 Dec 2007 23:02:39 GMT View Forum Message <> Reply to Message

Now work ok.

Another problem,

- I have radicore in 3 system:
- 1. IIS, path radicore E:\intranet\radicore\... work ok
- 2. xp + wamp work ok
- 3. IIS, path radicore C:\Inetpub\wwwroot\Intranet\radicore\... error before logon screen

My solution:/includes/config.inc \$_SERVER['DOCUMENT_ROOT']="C:\Inetpub\wwwroot";

The reason: In IIS, \$_SERVER['DOCUMENT_ROOT'] is empty.

Very grateful for your quick response.

Subject: Re: Problem with IIS Posted by AJM on Mon, 17 Dec 2007 23:17:07 GMT View Forum Message <> Reply to Message

\$_SERVER['DOCUMENT_ROOT'] is supposed to be defined in the server's configuration file. Does IIS not have a configuration file?

Subject: Re: Problem with IIS Posted by theos on Tue, 18 Dec 2007 10:08:56 GMT View Forum Message <> Reply to Message

In comments of user in http://www.php.net/reserved.variables:

\$_SERVER['DOCUMENT_ROOT'] *is* supported by IIS, although only when running PHP as an ISAPI module.

Two possible solutions

1.- How to get \$_SERVER["DOCUMENT_ROOT"] on IIS :

1.1.-

```
<?php
if ( ! isset($_SERVER['DOCUMENT_ROOT'] ) )
$_SERVER['DOCUMENT_ROOT'] = str_replace( '\\', '/', substr(
$_SERVER['SCRIPT_FILENAME'], 0, -strlen($_SERVER['PHP_SELF']) ) );
?>
1.2-
```

```
<?php
if(!isset($_SERVER["DOCUMENT_ROOT"]))
{$_SERVER["DOCUMENT_ROOT"]=substr($_SERVER['SCRIPT_FILENAME'],0,
-strlen($_SERVER['PHP_SELF'])+1);
}
?>
```

2.-

You can add \$_SERVER["DOCUMENT_ROOT"] to IIS by editing the Environment Variables of your Windows server (was tested on WinXP SP2).

Right click on My Computer >> Properties >> Advanced. In the System variables click on 'New' and Type in the name field 'DOCUMENT_ROOT' and in the value field the path to your IIS document root folder.

Don't forget to restart your Windows (IIS restart won't load the new settings).

Thank you for the support

Subject: Re: Problem with IIS Posted by AJM on Tue, 18 Dec 2007 10:55:50 GMT View Forum Message <> Reply to Message

I don't think it's a good idea to use \$_SERVER['PHP_SELF'] to provide a value for \$_SERVER['DOCUMENT_ROOT'] as a script may be run from any subdirectory below the root directory. This would make \$_SERVER['DOCUMENT_ROOT'] variable when in fact it is constant for the entire installation.

I never use any web server other than Apache (the industry standard) so I never encounter these problems.