
Subject: Incorrect CSS settings

Posted by [ljkbrost](#) on Fri, 14 Apr 2006 06:08:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

I run my apache server on http://localhost:8080 and I found a problem with the XML that gets sent to the client. It looks like the system is not sending the port for the machine.

```
<cssfiles> <filename>HTTP://localhost/radicore/style_default.css</filename>
<filename>HTTP://localhost/radicore/menu/style_custom.css</filename>
</cssfiles>
```

I have traced the problem to include.xml.php?.inc inside of the setCSSfiles(...) function. When building the filename values the string building function uses \$_SERVER['SERVER_NAME'] when it should use \$_SERVER['HTTP_HOST'].

Altering the code to the following resolved my problems:

```
// if no custom stylesheet is specified use 'style_custom.css' in local directory
if (empty($css_files)) {
    $css_files[] = 'HTTP://' . $_SERVER['HTTP_HOST'] . dirname($_SERVER['PHP_SELF'])
    .'/style_custom.css';
} // if

// prepend the default stylesheet name from base directory
$dir = getParentDIR();
if (!empty($_SERVER['HTTPS'])) {
    $default_css = 'HTTP://' . $_GLOBALS['https_server'] . $_GLOBALS['https_server_suffix'] . $dir
    .'/style_default.css';
} else {
    $default_css = 'HTTP://' . $_SERVER['HTTP_HOST'] . $dir .'/style_default.css';
} // if
```

Cheers,

Kyle Brost

Subject: Re: Incorrect CSS settings

Posted by [AJM](#) on Fri, 14 Apr 2006 10:05:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

Thanks for spotting that. It's always confusing when to use \$_SERVER['HTTP_HOST'] and \$_SERVER['SERVER_NAME'] as they supposedly give the same results except under circumstances which are not documented.

I shall change my code for the next release.
