Subject: Re: Installation problem with Parallels Plesk
Posted by htManager on Wed, 21 May 2014 09:59:02 GMT
View Forum Message <> Reply to Message

Hi Tony,

thank you very much for the quick reply.

I have checked the following things:

Existing databases: MGH_AUDIT, MGH_MENU, MGH_HTM, MGH_DICT, MGH_WORKFLOW

The user MGH_HTM_USER01 exists.

The account name is mgh.

I have checked the connection with both phpmyadmin and the following script:

```
/* Datenbankserver - In der Regel die IP */
$db_server = 'ip-address';

/* Datenbankname */
$db_name = 'MGH_AUDIT';

/* Datenbankuser */
$db_user = 'MGH_HTM_USER01';

/* Datenbankpasswort */
$db_passwort = 'password';

/* Erstellt Connect zu Datenbank her */
$db = @ mysql_connect ( $db_server, $db_user, $db_passwort )
   or die ( 'Konnte keine Verbindung zur Datenbank herstellen' );

echo "<p> Encoding wird eingestellt.</p>";

/* Einstellen des richtigen Encodings */
mysql_query("SET NAMES 'utf8'");

$db_check = @ mysql_select_db ( $db_name );

$res = mysql_query('select * from audit_tbl');
$num = mysql_num_rows($res);

/*if ($num > 0)
{
 // Tabellenbeginn
 echo "<table border = '0'>";
```

```
 // Ãœberschrift
 echo "<tr><td> </td><td>Session</td>";
 echo "<td>Transaktion</td><td>Datenbank</td>";

 while ($dsatz = mysql_fetch_assoc($res))
 {

  echo "<tr>";
  echo "<td><input type='radio' name='auswahl'";
  echo " value='"
   . $dsatz["session_id"] . "'/></td>";
  echo "<td>" . $dsatz["tran_seq_no"] . "</td>";
  echo "<td>" . $dsatz["table_seq_no"] . "</td>";
  echo "<td>" . $dsatz["base_name"] . "</td>";
  echo "</tr>";
 }

 echo "</table>";
}
else
{
 echo "Es gibt keine DatensÃ¤tze in Tabelle AUDIT_TBL.";
}
*/
```

I inserted a record in the table and I got the result in my browser.

Is there a problem with the dbprefix?

Regards,

Juergen