Subject: Re: Tree structure
Posted by htManager on Sat, 28 Feb 2015 13:31:20 GMT
View Forum Message <> Reply to Message

I suppose that the queries are generated in the _cm_getNodeData of the class file. I copied the code from the xample file and tried to change it. But I haven't much experience in generating SQL-queries, so that I suppose that I did something wrong. Especially because I have a primary key consisting of several fields. Here is my code, maybe you can see what I am doing wrong:

```
        $this->sql_select  =  'hallen_plaetze_nodes.node_id, '
          . 'hallen_plaetze_nodes.hallen_plaetze_node_desc, '
          . 'hallen_plaetze_nodes.hallen_plaetze_nodes_logo_fname, '
          . 'hallen_plaetze_level.hallen_plaetze_level_seq, '
          . 'COUNT(child.node_id) AS child_count';
        $this->sql_from    = 'hallen_plaetze_nodes '
                          .  'LEFT JOIN hallen_plaetze_level ON '
                          .  '(hallen_plaetze_level.verbaende_art_id=hallen_plaetze_nodes
.verbaende_art_id AND '
                          .  'hallen_plaetze_level.verbaende_kuerzel=hallen_plaetze_nodes
.verbaende_kuerzel AND '
                          .  'hallen_plaetze_level.halle_no=hallen_plaetze_nodes.halle_no AND '
                          .  'hallen_plaetze_level.hallen_plaetze_level_id=hallen_plaetze
_nodes.hallen_plaetze_level_id) '
                         . 'LEFT JOIN hallen_plaetze_nodes AS child ON
(hallen_plaetze_nodes.node_id=child.node_id_snr) ';
        $this->sql_where   = '';
        $this->sql_groupby =  'hallen_plaetze_nodes.node_id, '
          . 'hallen_plaetze_nodes.hallen_plaetze_node_desc, '
          . 'hallen_plaetze_nodes.hallen_plaetze_level_id, '
          . 'hallen_plaetze_level.hallen_plaetze_level_seq';
        $this->sql_having  = '';
        $this->sql_orderby =  'hallen_plaetze_nodes.hallen_plaetze_level_id,'
          . 'hallen_plaetze_nodes.node_id';
```