Subject: Re: SQLSRV Driver
Posted by rafs on Mon, 11 May 2015 12:12:00 GMT
View Forum Message <> Reply to Message

Same error as previously:
Fatal Error: [Microsoft][ODBC Driver 11 for SQL Server]Named Pipes Provider: Could not open a connection to SQL Server [53].
...

```
// this demonstrates the multi-server option (see FAQ92)
if (preg_match('/^(127.0.0.1|localhost|desktop|laptop)$/i', $_SERVER['SERVER_NAME'])) {
    global $servers;
    // server 0
    $servers[0]['dbhost']           = 'localhost';
    $servers[0]['dbengine']          = 'mysql';
    $servers[0]['dbusername']        = 'root';
    $servers[0]['dbuserpass']        = '';
    $servers[0]['dbport']           = '';
    $servers[0]['dbsocket']          = '';
    $servers[0]['dbprefix']          = '';
    $servers[0]['dbnames']           = 'audit,dict,menu,workflow';
    $servers[0]['ssl_key']           = '';
    $servers[0]['ssl_cert']          = '';
    $servers[0]['ssl_ca']           = '';
    $servers[0]['ssl_capath']        = '';
    $servers[0]['ssl_cipher']        = '';
    // server 1
    $servers[1]['dbhost']           = '10.100.150.86';
    $servers[1]['dbengine']          = 'sqlsrv';
    $servers[1]['dbusername']        = 'mydbusername';
    $servers[1]['dbuserpass']        = 'mydbpassword';
    $servers[1]['dbport']           = '';
    $servers[1]['dbsocket']          = '';
    $servers[1]['dbprefix']          = '';
    $servers[1]['dbnames']           = 'mydbname,*';
    $servers[1]['serverName']        = '(local)';
    $servers[1]['SQLSRV_schema']     = 'dbo';
    $servers[1]['connectionInfo']    = array('CharacterSet' => 'UTF-8',
                                'ReturnDatesAsStrings' => true);
} // if
```