Subject: ERROR: 22P02: invalid input syntax for integer
Posted by rafs on Thu, 27 Aug 2015 19:35:04 GMT
View Forum Message <> Reply to Message

My idps table:

```
CREATE TABLE idps (
    uid integer NOT NULL,
    idp_type character(3) NOT NULL,
    idp_id integer NOT NULL,
    idp_calc character varying(12) NOT NULL,
    idp_status integer DEFAULT 0 NOT NULL,
    created_date timestamp without time zone DEFAULT '2000-01-01 00:00:00'::timestamp without
time zone NOT NULL,
    created_user character varying(16) DEFAULT 'SYSTEM'::character varying NOT NULL,
    revised_date timestamp without time zone,
    revised_user character varying(16)
);

CREATE SEQUENCE idps_uid_seq    START WITH 1    INCREMENT BY 1    NO MINVALUE
NO MAXVALUE    CACHE 1;
ALTER TABLE ONLY idps ALTER COLUMN uid SET DEFAULT
nextval('idps_uid_seq'::regclass);
ALTER TABLE ONLY idps    ADD CONSTRAINT idps_pkey PRIMARY KEY (idp_type, idp_id);
ALTER TABLE ONLY idps    ADD CONSTRAINT idps_uid_key UNIQUE (uid);
ALTER TABLE ONLY idps ADD CONSTRAINT idps_idp_type_fkey FOREIGN KEY (idp_type)
REFERENCES idp_types(idp_type);
```

The Error:

```
Fatal Error: PostgreSQL: ERROR: 22P02: invalid input syntax for integer: "" LINE 1: SELECT
count(*) FROM idps WHERE uid='' ^ LOCATION: pg_atoi, numutils.c:52
SQL query: SELECT count(*) FROM idps WHERE uid=''
Error in line 578 of file 'C:\xampp\radicore\includes\dml.pgsql.class.inc'.
```

I tried: (1) removing the unique index from uid in the db, (2) removing
"nextval('idps_uid_seq'::regclass)" as the default value in the
RADICORE>>DB>>TABLE:idps>>COL:uid>>Default value field.
Neither worked.