Subject: PopUpForm
Posted by htManager on Fri, 06 Jun 2014 15:09:34 GMT
View Forum Message <> Reply to Message

Hi Tony,
I have created a popUp Task which shows me the entries of a lookup table and inserts the PKey-Fields (user_id, user_seq_no) in the child table.
Now I want to get additional field values (user_name, user_firstname) from the parent table for also inserting in the child table. The $select_array contains only the pkey values.
How can I get these additional values best?

Best regards,

Juergen

Subject: Re: PopUpForm
Posted by AJM on Fri, 06 Jun 2014 15:22:15 GMT
View Forum Message <> Reply to Message

By default the popup form will only return the primary key of the selected entry. There ate two ways to obtain other (non-key) values:
(1) Use the _cm_getPkeyNames() method in the popup form to add extra field names to the list of primary key fields.
(2) After returning to the form which called the popup you may insert code to read the record with that primary key. This will give you access to all the data on the selected record. You can put code in the _cm_popupReturn() method or the _cm_post_popupReturn() method.

Subject: Re: PopUpForm
Posted by htManager on Sat, 07 Jun 2014 11:29:04 GMT
View Forum Message <> Reply to Message

I try to get the data by adding these lines of code to my class file:

```
 function _cm_post_popupReturn ($fieldarray, $return_from, $select_array)
 {
       // get contents of foreign table HTM_DB_KONTAKTE
       $dbobject =& RDCsingleton::getInstance('htm_db_kontakte'); // Lookup-Tabelle
       $where = "kontakt_name=$select_array['user_id'] AND
kontakt_vorname=$select_array['user_seq_no']";
       $array = $dbobject->_dml_getData ($where);     // PKey-Felder

  $fieldarray['kontakt_ma_name'] = $array['kontakt_name'];
  $fieldarray['kontakt_ma_vorname'] = $array['kontakt_vorname'];

  return $fieldarray;
```

```
}
```

I am not so familiar with PHP and OO Programming although I read a lot but doing it is something different. That's why I am absolutely not sure if this is the right way.
Can you give me some advice?

Subject: Re: PopUpForm
Posted by AJM on Sat, 07 Jun 2014 12:18:29 GMT
View Forum Message <> Reply to Message

Do not use the $dbobject_dml_getData() method , use $dbobject->getData() instead.

When you construct the WHERE string you must remember to enclose non-numeric values with single quotes.

The result returned by getData() is a 2-dimensional array which is keyed by row numnber, with the value being an associative array of name=value pairs. Your code should therefore look like this:

```
$dbobject =& RDCsingleton::getInstance('htm_db_kontakte');
$where = "kontakt_name='{$select_array['user_id']}' AND
kontakt_vorname='{$select_array['user_seq_no']}'";
$data = $dbobject->getData ($where);
if (!empty($data) {
    $data = $data[0];
    $fieldarray['kontakt_ma_name'] = $data['kontakt_name'];
    $fieldarray['kontakt_ma_vorname'] = $data['kontakt_vorname'];
} // if
```

Subject: Re: PopUpForm
Posted by htManager on Sat, 07 Jun 2014 17:13:57 GMT
View Forum Message <> Reply to Message

Thank you very much. It works perfectly!
