
Subject: Help/suggestions with record filtering by user
Posted by [bonzo_bcn](#) on Wed, 09 Jul 2008 19:45:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

I have table called 'people' that stores personal data (name, address etc.).
This table is filled by two types of users: schools and super_schools.

Each school should only be able to see the persons they have created, super_schools must see all records.

One same people record can be created by many schools: in this case the first one would do an insert and the following transactions would do nothing (or maybe update), but the second and third schools should also be able to see the 'people' record.

What do you suggest for this scenario?

Subject: Re: Help/suggestions with record filtering by user
Posted by [AJM](#) on Wed, 09 Jul 2008 21:19:30 GMT
[View Forum Message](#) <> [Reply to Message](#)

How do you identify the difference between 'school' users and 'super_school' users?

How can you identify that the current user belongs to the 'school' or 'super_school' category?

How can you identify the category of a user who created a record?

Subject: Re: Help/suggestions with record filtering by user
Posted by [bonzo_bcn](#) on Thu, 10 Jul 2008 08:40:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

AJM wrote on Wed, 09 July 2008 17:19How do you identify the difference between 'school' users and 'super_school' users?
By role

How can you identify that the current user belongs to the 'school' or 'super_school' category?
My idea is to have a table with schools and that each school user's role is the same as the school name in the table. So to identify a school I can look for a record in 'schools' with name=user_role.

How can you identify the category of a user who created a record?
Same as above, check if their user_role is in the school table

Does that seem ok?

Subject: Re: Help/suggestions with record filtering by user

Posted by [AJM](#) on Thu, 10 Jul 2008 09:26:28 GMT

[View Forum Message](#) <> [Reply to Message](#)

If you are hoping that there is something in the Radicore framework that will achieve this automatically then you are out of luck. There are only two levels of security available:

(1) Task-level security, where a user either has permission to access a task, or he doesn't. When running a task there are no restrictions on which data can or cannot be accessed.

(2) In some cases several accounts can share the same database, but users within an account are restricted to data owned by that account. The data within the shared database is said to be partitioned by account. This can be implemented using the procedures documented in <http://www.tonymarston.net/php-mysql/virtual-private-databases.html>.

Item (1) is a fundamental feature of Radicore and cannot be turned off. Item (2) is entirely optional and can be turned on when required.

What you seem to be asking for is outside the scope of either of these options, so cannot be implemented without changes in your database design and the addition of custom code.

Each 'person' record is restricted to a particular group of users, but can also be viewed by a 'super' user. This means that you must have a column on the 'person' table which identifies the class of the user who created it. Then when reading from the 'person' table you must identify the class of the user, and if he is 'restricted' you must add the following to the WHERE clause of the sql SELECT statement:

```
... AND class='user_class'
```

This can be done by adding the relevant code in the `_cm_pre_getData()` method.

In short, the framework cannot do what you want automatically, but it does not prevent you from inserting custom code which is tailored to your needs.

Subject: Re: Help/suggestions with record filtering by user

Posted by [bonzo_bcn](#) on Thu, 10 Jul 2008 10:41:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

sure it doesn't do what I want out of the box, I didn't expect that I'm trying a workaround, but I'm stuck here, maybe you can help:
When a school creates a person I use `_cm_post_insertRecord` to automatically insert a record in `pers_school_xref` with the `person_id` and the `user_role`, this way I know that the users that have that `user_role` can see the records.

The problem arises when a second school wants to create the same person, I'm trying to find a way in that no data is inserted in the person table, but a record is created in `pers_school_xref` with the `person_id` and the second school `user_role`.

I've tried to use `_cm_post_insertRecord` to check if the record exists, and if it does, then insert a record in `pers_school_xref` and launch an error message 'Person already created' so that the person is not inserted again, but it is assigned to this school, the problem is that it rolls back the insert in `pers_school_xref`.

Is there a way to save the record in `pers_school_xref` but not in person when a school tries to insert in person table?

Subject: Re: Help/suggestions with record filtering by user

Posted by [AJM](#) on Thu, 10 Jul 2008 11:07:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

If you put anything into `$this->errors` then the update is deemed to have failed, in which a rollback will automatically be performed. If you want to issue a message which is not an error then use `$this->messages` instead.

If you want to prevent the insert of a duplicate record for a person then doing it in the `_cm_post_insertRecord()` method is too late as that is performed AFTER the insert. You should use the `_cm_validateInsert()` method which is performed BEFORE the insert. If you discover that the record is a duplicate then return an empty array - this will cause the INSERT to be skipped, but the original data will still be available in the `_cm_post_insertRecord()` method so that you can update the `pers_school_xref` table.

Subject: Re: Help/suggestions with record filtering by user

Posted by [bonzo_bcn](#) on Thu, 10 Jul 2008 12:35:28 GMT

[View Forum Message](#) <> [Reply to Message](#)

Thanks for your help.

How can I access the original data in `_cm_post_insertRecord()`?

If the validation returns an empty array isn't the array that arrives as parameter to `post_insertrecord` empty?.

Subject: Re: Help/suggestions with record filtering by user

Posted by [AJM](#) on Thu, 10 Jul 2008 13:03:14 GMT

[View Forum Message](#) <> [Reply to Message](#)

If you look inside the `insertRecord()` method you will see that `$fieldarray` is copied to `$insertarray`, and while `$insertarray` is used by the `_cm_validateInsert()` method it is `$fieldarray` which is used by the `_cm_post_insertRecord()` method.

Subject: Re: Help/suggestions with record filtering by user

I must be doing something wrong because in post_insertRecord I get a NULL value for \$fieldarray['participante_id'];
Any idea why?

```
function _cm_validateInsert($rowdata){

    $part = new participante;
    $existe_participante = $part->getCount("catsalut='".$rowdata['catsalut']."'");

    if ($existe_participante > 0){

        $this->messages['participante_existe'] = "Participante ya dado de alta en el sistema, no se han
modificado datos existentes";
        return null;
    }
    return $rowdata;
}

function _cm_post_insertRecord($fieldarray)

{
    require_once 'classes/entidad.class.inc';
    $entidad = new entidad;
    $entidad->sql_select = 'entidad_id';
    $entidad_id = $entidad->getData("nombre='" .$_SESSION['role_id'] ."'");

    require_once 'classes/part_ent_xref.class.inc';
    $part_ent_xref = new part_ent_xref;
    $insert_array['participante_id'] = $fieldarray['participante_id'];
    $insert_array['entidad_id'] = $entidad_id[0]['entidad_id'];

    $insert_array = $part_ent_xref->insertOrUpdate($insert_array);

    if ($part_ent_xref->errors){
        $this->errors = $part_ent_xref->errors;
        return $fieldarray;
    }
    return $fieldarray;
}
```

Subject: Re: Help/suggestions with record filtering by user

Posted by [AJM](#) on Thu, 10 Jul 2008 13:56:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

Is that value in the array that is passed TO the insertRecord() method? If not, where does it come from?

Subject: Re: Help/suggestions with record filtering by user

Posted by [bonzo_bcn](#) on Thu, 10 Jul 2008 14:12:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

participante_id is a field of the record that is being inserted. It is an autoincrement and the primary key of the table, so now I see why it's null. Anyway I tried adding this code:

```
if (is_null($fieldarray['participante_id'])) {
    $part = new participante;
    $part->sql_select = 'participante_id';
    $participante_id = $part->getData("catsalut='".$fieldarray['catsalut']."'");
} else {
    $participante_id = $fieldarray['participante_id'];
}
```

to

```
function _cm_post_insertRecord($fieldarray)
{
    require_once 'classes/entidad.class.inc';
    $entidad = new entidad;
    $entidad->sql_select = 'entidad_id';
    $entidad_id = $entidad->getData("nombre=" . $_SESSION['role_id'] . "");

    require_once 'classes/part_ent_xref.class.inc';
    $part_ent_xref = new part_ent_xref;

    if (is_null($fieldarray['participante_id'])) {
        $part = new participante;
        $part->sql_select = 'participante_id';
        $participante_id = $part->getData("catsalut='".$fieldarray['catsalut']."'");
    } else {
        $participante_id = $fieldarray['participante_id'];
    }
}
```

```

}

$insert_array['participante_id'] = $participante_id;
$insert_array['entidad_id'] = $entidad_id[0]['entidad_id'];
$insert_array = $part_ent_xref->insertOrUpdate($insert_array);

if ($part_ent_xref->errors){
    $this->errors = $part_ent_xref->errors;
    return $fieldarray;
}
return $fieldarray;
}

```

but I get a null value in \$fieldarray['catsalut'], catsalut is a field of the record that is being added.

Your help is really appreciated.

Subject: Re: Help/suggestions with record filtering by user
 Posted by [AJM](#) on Thu, 10 Jul 2008 15:06:01 GMT
[View Forum Message](#) <> [Reply to Message](#)

You are confusing me. If 'participante_id' is filled in when a new record is created then you are creating a NEW record and not preventing the creation of a duplicate.

If you require this to be the value from an existing record (ie: the record for which this would be a duplicate) then you must have code which reads the database to provide this value. If this code is already in the _cm_validateInsert() method and you do not want to duplicate in the cm_post_insertRecord() method then you must save it in a class variable so that it is available without being passed in one of the arguments.

Subject: Re: Help/suggestions with record filtering by user
 Posted by [AJM](#) on Thu, 10 Jul 2008 15:09:35 GMT
[View Forum Message](#) <> [Reply to Message](#)

Where does the value for 'catsalut' come from? Is it within the \$fieldarray which is passed into the insertRecord() method?

Subject: Re: Help/suggestions with record filtering by user
 Posted by [bonzo_bcn](#) on Thu, 10 Jul 2008 15:27:37 GMT
[View Forum Message](#) <> [Reply to Message](#)

I think so. 'catsalut' is a field of the record that is being pseudo-created (the user is trying to create it but it will only create a record in the xref table).

I've implemented a class variable and the problem was solved. Thanks a million.
