

---

Subject: Database/Table Import Error

Posted by [ljkbrost](#) on Thu, 05 Nov 2009 22:52:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Radicore Version: 1.53.0

I cannot import the databases for a new subsystem. The radicore framework dies with a fatal error and I have attached the errorlog.html to this message.

Upon investigation it looks like it has to do with the database prefix. My tables are prefixed with 'dev1\_' and when I go to import the database the system recognizes the missing DB and starts the import. When it gets to the tables it looking for 'dev1\_dev1\_customer'. It should be 'dev1\_customer'.

Looking at dict\_table\_s01.class.inc the problem appear on line 25:

```
$fieldarray = array();  
$array = $this->_ddl_showTables($dbprefix.$dbname);
```

The system is trying to 'showTables' for 'dev1\_' . 'dev1\_customer'. Removing the \$dbprefix from the line fixes the problem and allows me to import the database and tables with no problem. The \$dbname already is fully qualified with the prefix.

Cheer,

Kyle Brost

---

### File Attachments

1) [errorlog.html](#), downloaded 696 times

---

---

Subject: Re: Database/Table Import Error

Posted by [ljkbrost](#) on Thu, 05 Nov 2009 23:44:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

It looks like this problem is also happening with:

dict\_column\_s01.class.inc

On a quick check on the directory there are a lot of dbprefix variables used in the various tables. Not sure if there will be any other issues.

Cheers,

Kyle Brost

----

---

Subject: Re: Database/Table Import Error  
Posted by [AJM](#) on Fri, 06 Nov 2009 10:43:12 GMT  
[View Forum Message](#) <> [Reply to Message](#)

I have tried this on my PC and I cannot reproduce the fault. It may be because of something in your config.inc file, so can you post me its contents? You can block out your username and password.

The way the \$dbprefix feature is supposed to work is as follows:

- you have a database called 'foobar'
- it is imported into the data dictionary as 'foobar'
- you may create a copy of this database called 'dev1\_foobar', but in order to access it your config.inc file should identify it as \$dbname='foobar' and \$dbprefix='dev1\_'
- the dictionary import functions will use \$dbprefix to access the database schema, but will use only \$dbname within the dictionary database.

This means that you can have as many copies of 'foobar' as you like, such as 'dev1\_foobar', 'dev2\_foobar', 'this\_foobar' and 'that\_foobar', but the data dictionary will only have one set of details under the name 'foobar'. At runtime you can only access one of these databases, so you set the value of \$dbprefix in your config.inc file accordingly.

If the dbname in the data dictionary includes the dbprefix then you have done something wrong.

I did find one small problem in the dict\_table\_key class, so I have attached an updated file.

### File Attachments

1) [dict\\_table\\_key.class.zip](#), downloaded 1841 times

---

Subject: Re: Database/Table Import Error  
Posted by [ljkbrost](#) on Fri, 06 Nov 2009 14:12:46 GMT  
[View Forum Message](#) <> [Reply to Message](#)

The password doesn't matter as the system is a development box.

```
if (eregi('^(127.0.0.1|localhost|desktop|laptop)$', $_SERVER['SERVER_NAME'])) { // this is for
my PC
    $GLOBALS['dbusername'] = '****';
    $GLOBALS['dbuserpass'] = '****';
    $GLOBALS['dbprefix'] = null;
    // set these only if secure HTTPS protocol is available on your server
    $GLOBALS['http_server'] = "";
    $GLOBALS['https_server'] = "";
```

```
$GLOBALS['https_server_suffix'] = "";
} else {
    // this is for my shared web host
    $GLOBALS['dbusername'] = 'radicore';
    $GLOBALS['dbuserpass'] = 'radi.core.2009';
    $GLOBALS['dbprefix'] = 'dev1_';
    // set these only if secure HTTPS protocol is available on your server
    $GLOBALS['http_server'] = "";
    $GLOBALS['https_server'] = "";
    $GLOBALS['https_server_suffix'] = "";
} // if
```

The naming of the databases:

```
dev1_audit
dev1_customer
dev1_dict
dev1_menu
dev1_workflow
```

I am running PHP 5.3.

Cheers,

Kyle Brost

----

[www.softelephant.com](http://www.softelephant.com)

---

---

Subject: Re: Database/Table Import Error  
Posted by [AJM](#) on Fri, 06 Nov 2009 14:43:56 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

There is nothing wrong with your config.inc file, and I cannot reproduce this fault on my PC.

The problem lies somewhere in the `_loadDatabases()` method inside `'dict_dataBase_s01.class.inc'` where it looks for database names with the prefix, then strips off the prefix for internal use. All database names which appear in the dropdown list should not include the prefix.

You need to step through with your debugger to see what the code is doing with the prefix.

---

---

Subject: Re: Database/Table Import Error  
Posted by [ljkbrost](#) on Fri, 06 Nov 2009 15:27:08 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is what `$this->_ddl_showDatabases($dbprefix)`

```
Array ( [0] => dev1_audit
        [1] => dev1_customer
        [2] => dev1_dict
        [3] => dev1_menu
        [4] => dev1_workflow )
```

`$dbnames` contains:

```
Array ( [customer] => customer )
```

See no issue there.

Drilling down into `dict_table_s01` the `_cm_getInitialDataMultiple` function ultimately calls `$this->_ddl_showTables`. Inside the MySQL, MySQLi, and PgSql versions the function grabs the `dbprefix` from `$GLOBALS`. Looking at the Oracle versions there is no reference to the `dbprefix` in the file.

Are you using the Oracle version and hence the reason things work for you and not me? I don't have oracle installed anywhere to test this out.

I know the `dbprefix` gets appended in `dict_table_s01` as well in the mysql calls to `_ddl_showTables`. Hence the doubling up of `dbprefix`.

Hope that helps,

Kyle Brost

----

[www.softelephant.com](http://www.softelephant.com)

---

Subject: Re: Database/Table Import Error  
Posted by [AJM](#) on Fri, 06 Nov 2009 17:49:51 GMT  
[View Forum Message](#) <> [Reply to Message](#)

I do all my development and testing with MySQL, which is what I assume you are using. I only play with the PostgreSQL and Oracle databases when a problem arises, or when introducing new functionality.

If the output from the call to `_loadDatabases()` is a `dbname` of 'customer', then where does the 'dev1\_' prefix get added in twice? I have just tried it on my system by erasing the details of a database with a prefix, then importing it again, and it worked flawlessly (apart from the bug I fixed earlier ).

Can you step through with your debugger to see where the prefix is being used twice?

---

Subject: Re: Database/Table Import Error  
Posted by [ljkbrost](#) on Fri, 06 Nov 2009 18:42:59 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Inside: dml.mysql.class.inc

```
function ddl_showTables ($dbname)
// obtain a list of tables within the specified database.
{
    // connect to database
    $this->connect($dbname) or trigger_error($this, E_USER_ERROR);

    $array = array();

    $dbname = $GLOBALS['dbprefix'] . $dbname;

    // build the query string and run it
    $this->query = 'SHOW TABLES FROM "' . $dbname . '"';

    $result = mysqli_query($this->dbconnect, $this->query) or trigger_error($this,
E_USER_ERROR);

    $count = mysqli_num_rows($result);

    // write query to log file, if option is turned on
    logSqlQuery ($dbname, null, $this->query, $count);

    // convert result set into a simple indexed array for each row
    while ($row = mysqli_fetch_row($result)) {
        $array[] = $row[0];
    } // while

    mysqli_free_result($result);

    return $array;
} // ddl_showTables
```

Notice the \$dbname variable gets reassigned to:  
\$dbname = \$GLOBAL['dbprefix'] . \$dbname;

When it comes into this function it already has the dbprefix attached to it from the  
\_cm\_getInitialDataMultiple function of dict\_table\_s01.class.inc. (Noted below).

```
function _cm_getInitialDataMultiple ($fieldarray)
// Perform custom processing prior to insertMultiple.
// $fieldarray contains data from the initial $where clause.
```

```

{
// get list of existing table names
if (!is_string(key($fieldarray))) {
    $fieldarray = $fieldarray[0];
} // if

$dbname = $fieldarray['database_id'];
$dbprefix = dict_findDBPrefix($dbname);

$array = $this->_ddl_showTables($dbprefix.$dbname);

// filter out those that already exist in DICT database
$i = 0;
foreach ($array as $tablename) {
    $tablename = strtolower($tablename);
    $count = $this->getCount("database_id='$dbname' AND table_id='$tablename'");
    if ($count == 0) {
        // insert details of new database
        $fieldarray[$i]['database_id'] = $dbname;
        $fieldarray[$i]['table_id'] = $tablename;
        $fieldarray[$i]['table_desc'] = ucwords(str_replace('_', ' ', $tablename));
        $i++;
    } // if
} // foreach

return $fieldarray;

} // _cm_getInitialDataMultiple

```

The call to `$this->_ddl_showTables($dbprefix.$dbname);` adds the prefix and then the call within `Default_Table::_ddl_showTables` that calls `mysql::ddl_showTables` does the same thing. Hence the double append.

Does that help?

Kyle Brost

----

[www.softelephant.com](http://www.softelephant.com)

Subject: Re: Database/Table Import Error  
 Posted by [AJM](#) on Fri, 06 Nov 2009 20:49:21 GMT  
[View Forum Message](#) <> [Reply to Message](#)

Ah ha! I've found the problem. I was using a config.inc file which used the multiple servers option,

as described in FAQ92. This had a value for `$servers[0]['dbprefix']` but nothing for `$GLOBALS['dbprefix']`, so I didn't spot that `dbprefix` was being added in twice.

The solution is to remove the following line

```
$dbname = $GLOBALS['dbprefix'].$dbname;
```

from the `ddl_showColumns()` and `ddl_showTables()` methods inside your copy of the `'dml.mysql[i].class.inc'` file.

An updated copy of `'dml.mysql[i].class.inc'` is attached.

### File Attachments

1) [dml.mysql\[i\].class.zip](#), downloaded 1800 times

---