
Subject: AUTO transitions

Posted by [ljkbrost](#) on Mon, 05 Apr 2010 04:42:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi,

I have created auto transitions for the sending of emails after the completion of tasks. Everything works great in the 'simple' case. But...

I have a sequence of scripts that get called in the order:

- 1) add1
- 2) upd1
- 3) add1

In the `_cm_postInsertRecord()` and `_cm_postUpdateRecord()`, I have placed a call to `append2ScriptSequence` so that they 'jump' to the next task. Works great!

When I attach a workflow so that an email is sent after each step, the workflow gets hung (no errors) and the sequence works normally. Researching this I have found the the workflow does a similar `append2ScriptSequence()`. When this happens I get:

```
(
  [0] => Array
    (
      [task_id] => step2
      [where] => participant_id='593d-ed0b-7eb1ff0f2110836-2bb949'
      [inserted_by] => step1
    )

  [1] => Array
    (
      [task_id] => send_email
      [where] => participant_id='593d-ed0b-7eb1ff0f2110836-2bb949'
    )
)
```

When this executes the 'send_email' function gets lost or only completed at the end of all the tasks. Not a desirable thing as we want emails at the end of each task and not all tasks.

Reviewing the design document on workflows, it makes sense that workflows should always fire before 'business logic navigation control' as the workflow needs to operate unaware of how the various tasks are actually implemented.

If I change the ordering of the logic in 'examineInwardArc(...)' so that all workflow transitions are

given priority (at the head of the array), things work as I would expect them to.

I think this is an area that should be altered to make the workflow take priority of the sequence of events and potentially the code should be updated to make use of a similar `append2ScriptSequence` versus using things hard coded.

This is my modified code in `wf_arc.class.inc` to make it work.

```
if ($arc_data['transition_trigger'] == 'AUTO') {  
    // trigger is 'AUTO', so commit current updates and process this workitem now  
    $this->errors = $dbworkitem->commit();  
    $next['task_id'] = $arc_data['task_id'];  
    $next['where'] = $arc_data['context'];  
  
    $current = $_SESSION['script_sequence'];  
    $_SESSION['script_sequence'] = array();  
    $_SESSION['script_sequence'][] = $next;  
    foreach($current as $next)  
    {  
        $_SESSION['script_sequence'][] = $next;  
    }  
  
    // terminate current script and activate designated task  
  
    scriptPrevious();  
} // if
```

I think it would also be good to add 'inserted_by' in the sequence array. It would have saved me a bunch of time tracing this and it make sense.

Cheers!

Kyle Brost

www.softtelephant.com

Subject: Re: AUTO transitions

Posted by [AJM](#) on Mon, 05 Apr 2010 09:01:57 GMT

[View Forum Message](#) <> [Reply to Message](#)

Good idea. I've changed this code to use the `append2ScriptSequence()` function which automatically adds 'inserted_by' (the current task_id) to the array. I have also added a second argument to this function which will cause it to prepend instead of append to the `$_SESSION['script_sequence']` array.
